

GAS FURNACES

80% | 96%



OXBOX™
A TRANE® BRAND

When the weather gets chilly, you'll get comfortable, consistent heating—and you can also be confident these furnaces are built for durable performance over the long haul.



Our enhanced warranty gives you maximum peace of mind. Plus, every piece of equipment is warranted to the home, not the homeowner — providing an extra measure of coverage when it comes time to sell.

WARRANTIES AVAILABLE:

- 1 year unit replacement.*
- 10 year warranty on parts with product registration.
- 20 year heat exchanger.
- Warranty stays with the home.

Base warranty is still available without registration.

*If the compressor, coil or heat exchanger fails in the first year.

Questions? Go to OXBOXHVAC.COM for more information.

80% Single Stage Upflow/Downflow/Horizontal Right/Left

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J801V040AM3SE*	80%	40,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 14.5 x 28.5
J801V060AM3SE*	80%	60,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 14.5 x 28.5
J801V060BM4SE*	80%	60,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 17.5 x 28.5
J801V080BM4SE*	80%	80,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 17.5 x 28.5
J801V080CM4SE*	80%	80,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 21.0 x 28.5
J801V100CM5SE*	80%	100,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 21.0 x 28.5
J801V120DM5SE*	80%	120,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 24.5 x 28.5

J801V Accessories

Part Number	Description
JAYHAKFURN801VA	High Altitude Kit, 80% Furnace

- Furnace models feature aluminized steel heat exchangers to conduct heat quickly and increase durability
- Oxbox furnaces are designed for multi-position installation allowing for easy replacement or new construction installations
- Furnaces are fully convertible to either natural gas or propane, making them suitable for use in any area - LP kit included
- Painting galvanized steel cabinet that passed 500 hour salt spray test
- Quiet, multi-speed ECM circulator blower motor
- Oxbox furnaces are built for flexibility to suit varied installations and comply with Energy Star cabinet air leakage requirement of less than or equal to 2% (J801V*SEB Models Only)

For installation in SCAQMD only: The J801V NOx emission level is >40 ng/J and can't be sold and/or installed where State and/or District regulations require <40 ng/J.



GAS FURNACES

80% | 96%



J962X/962V ACCESSORIES (UPFLOW/ HORIZONTAL RIGHT/LEFT MODELS ONLY)

Part Number	Description
JAYHAKFURN962XA	High Altitude Kit, 96% Furnace

96% 2-STAGE VARIABLE SPEED UP UPFLOW/ HORIZONTAL RIGHT/LEFT

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J962V060BU3SAA	96%	60,000	Upflow/Horizontal Right/Left	(33.7 x 17.5 x 28.7)
J962V080BU3SAA	96%	80,000	Upflow/Horizontal Right/Left	(33.7 x 17.5 x 28.7)
J962V080CU4SAA	96%	80,000	Upflow/Horizontal Right/Left	(33.7 x 21.0 x 28.7)
J962V100CU5SAA	96%	100,000	Upflow/Horizontal Right/Left	(33.7 x 21.0 x 28.7)
J962V100DU5SAA	96%	100,000	Upflow/Horizontal Right/Left	(33.7 x 24.5 x 28.7)
J962V120DU5SAA	96%	120,000	Upflow/Horizontal Right/Left	(33.7 x 24.5 x 28.7)

96% DUAL STAGE UPFLOW/HORIZONTAL RIGHT/LEFT

J962X060BU3SEA	96%	60,000	Upflow/Horizontal Right/Left	33.7 x 17.5 x 28.8
J962X080BU3SEA	96%	80,000	Upflow/Horizontal Right/Left	33.7 x 17.5 x 28.8
J962X080CU4SEA	96%	80,000	Upflow/Horizontal Right/Left	33.7 x 21.0 x 28.8
J962X100CU5SEA	96%	100,000	Upflow/Horizontal Right/Left	33.7 x 21.0 x 28.8
J962X100DU5SEA	96%	100,000	Upflow/Horizontal Right/Left	33.7 x 24.5 x 28.8
J962X120DU5SEA	96%	120,000	Upflow/Horizontal Right/Left	33.7 x 24.5 x 28.8

WARRANTIES AVAILABLE:

- 1 year unit replacement.*
- 10 year warranty on parts with product registration.
- 20 year heat exchanger.
- Warranty stays with the home.

Base warranty is still available without registration.

*If the compressor, coil or heat exchanger fails in the first year.

- Furnace models feature aluminized steel heat exchangers to conduct heat quickly and increase durability
- Oxbox furnaces are designed for multi-position installation allowing for easy replacement or new construction installations
- Twinning capability built in on J962X models only. No kit required
- Furnaces are fully convertible to either natural gas or propane, making them suitable for use in any area - LP kit included
- Painting galvanized steel cabinet that passed 500 hour salt spray test
- Quiet, multi-speed ECM circulator blower motor (J962V Models Only)
- Oxbox furnaces are built for flexibility to suit varied installations and comply with Energy Star cabinet air leakage requirement of less than or equal to 2%

For installation in SCAQMD only: These furnaces do not meet the SCAQMD Rule 1111 14 ng/J NOx emission limit and are only eligible for installation in high altitude (4,200 feet and above) or propane applications and are subject to a mitigation fee of up to \$450 USD. These furnaces are not eligible for the Clean Air Furnace Rebate Program: www.CleanAirFurnaceRebate.com.

Questions? Go to OXBOXHVAC.COM for more information.

